

ALPHA



Technical Data Sheet

Model T1C 160L-4

Housing material		Casting iron
Phase		Three
Frame size		160
Power(50Hz)	kW	15.00
Current(A)400V	Δ	28.06
Current(A)690V	Y	16.26
Speed(50Hz)	(r/min)	1450
Efficiency	IE1	
	Eff.100%	88.70
	Eff.75%	90.80
	Eff.50%	90.20
Power factor cosφ	100% load	0.87
60Hz 460/793V	Power(kW)	17.25
60Hz 480/830V	Power(kW)	18.00
Speed(60Hz)	(r/min)	1740
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	98.79
Tst/Tn (Times)	2.2
Tmax/Tn (Times)	2.6
Tmin/Tn (Times)	1.6
Ist/In (Times)	8
Bearings type(DE)	6309C3
Bearings type(NDE)	6309C3
Oil seals	45*65*8
Cable glands	2-M32*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	75
Net weight(kg)	137.00
Moment of inertia (kg*m²)	0.103790000



- Bearings & Seals
- Chains & Sprockets
- Electric Motors & Drives
- Belts & Pulleys
- Gearboxes & Couplings
- Lubricants & Tools
- Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za