

ALPHA



Technical Data Sheet

Model T1C 250M-4

Housing material		Casting iron
Phase		Three
Frame size		250
Power(50Hz)	kW	55.00
Current(A)525V	Δ	73.79
Current(A)550V	Δ	70.44
Speed(50Hz)	(r/min)	1480
Efficiency	IE1	
	Eff.100%	92.10
	Eff.75%	92.40
	Eff.50%	90.70
Power factor cosφ	100% load	0.89
60Hz 600V	Power(kW)	63
Speed(60Hz)	(r/min)	1776
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	354.90
Tst/Tn (Times)	2.2
Tmax/Tn (Times)	2.6
Tmin/Tn (Times)	1.3
Ist/In (Times)	8
Bearings type(DE)	6314C3
Bearings type(NDE)	6314C3
Oil seals	95*70*10
Cable glands	2-M50*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	83
Net weight(kg)	397.00
Moment of inertia (kg*m²)	0.690980000



- Bearings & Seals
- Chains & Sprockets
- Electric Motors & Drives
- Belts & Pulleys
- Gearboxes & Couplings
- Lubricants & Tools
- Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za