

ALPHA



Technical Data Sheet

Model T1C 315L2-2

Housing material		Casting iron
Phase		Three
Frame size		315
Power(50Hz)	kW	110,00
Current(A)400V	Δ	200,20
Current(A)690V	Y	115,58
Speed(50Hz)	(r/min)	980
Efficiency	IE1	
	Eff.100%	93,30
	Eff.75%	93,50
	Eff.50%	92,30
Power factor cosφ	100% load	0,85
60Hz 460/793V	Power(kW)	126,50
60Hz 480/830V	Power(kW)	132,00
Speed(60Hz)	(r/min)	1176
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	1071,94
Tst/Tn (Times)	1,8
Tmax/Tn (Times)	2,2
Tmin/Tn (Times)	2,2
Ist/In (Times)	7
Bearings type(DE)	NU319 C3
Bearings type(NDE)	6319 C3
Oil seals	85*110*12
Cable glands	2-M63*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	85
Net weight(kg)	965,00
Moment of inertia (kg*m²)	1,906230000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za