

ALPHA



Technical Data Sheet

Model T1C 180M-2

Housing material		Casting iron
Phase		Three
Frame size		180
Power(50Hz)	kW	11,00
Current(A)400V	Δ	23,74
Current(A)690V	Y	13,71
Speed(50Hz)	(r/min)	730
Efficiency	IE1	
	Eff.100%	88,00
	Eff.75%	87,30
	Eff.50%	84,40
Power factor cosφ	100% load	0,76
60Hz 460/793V	Power(kW)	12,65
60Hz 480/830V	Power(kW)	13,20
Speed(60Hz)	(r/min)	876
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	143,90
Tst/Tn (Times)	2,2
Tmax/Tn (Times)	2,3
Tmin/Tn (Times)	1,4
Ist/In (Times)	6,6
Bearings type(DE)	6311C3
Bearings type(NDE)	6311C3
Oil seals	55*75*8
Cable glands	2-M32*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	70
Net weight(kg)	174,00
Moment of inertia (kg*m²)	0,081100000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za