

ALPHA



Technical Data Sheet

Model T1C 200L2-6

Housing material		Casting iron
Phase		Three
Frame size		200
Power(50Hz)	kW	22,00
Current(A)400V	Δ	43,41
Current(A)690V	Y	25,06
Speed(50Hz)	(r/min)	970
Efficiency	IE1	
	Eff.100%	89,20
	Eff.75%	91,00
	Eff.50%	90,50
Power factor cosφ	100% load	0,82
60Hz 460/793V	Power(kW)	25,30
60Hz 480/830V	Power(kW)	26,40
Speed(60Hz)	(r/min)	1170
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	216,60
Tst/Tn (Times)	2,3
Tmax/Tn (Times)	2,5
Tmin/Tn (Times)	2,5
Ist/In (Times)	7,5
Bearings type(DE)	6312 C3
Bearings type(NDE)	6312 C3
Oil seals	60*80*8
Cable glands	2-M40*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	76
Net weight(kg)	218,20
Moment of inertia (kg*m²)	0,394450000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za