

ALPHA



Technical Data Sheet

Model T1C 250M-8

Housing material		Casting iron
Phase		Three
Frame size		250
Power(50Hz)	kW	30,00
Current(A)400V	Δ	60,23
Current(A)690V	Y	34,77
Speed(50Hz)	(r/min)	740
Efficiency	IE1	
	Eff.100%	91,00
	Eff.75%	91,90
	Eff.50%	90,80
Power factor cosφ	100% load	0,79
60Hz 460/793V	Power(kW)	34,50
60Hz 480/830V	Power(kW)	36,00
Speed(60Hz)	(r/min)	1170
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	387,16
Tst/Tn (Times)	1,9
Tmax/Tn (Times)	2
Tmin/Tn (Times)	2
Ist/In (Times)	6,6
Bearings type(DE)	6314 C3
Bearings type(NDE)	6314 C3
Oil seals	95*70*10
Cable glands	2-M50*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	75
Net weight(kg)	395,00
Moment of inertia (kg*m²)	1,020084976



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za