

ALPHA



Technical Data Sheet

Model T2C 280S-6

Housing material		Casting iron
Phase		Three
Frame size		280
Power(50Hz)	kW	45,00
Current(A)400V	Δ	83,60
Current(A)690V	Y	48,27
Speed(50Hz)	(r/min)	980
Efficiency	IE2	
	Eff.100%	91,40
	Eff.75%	92,60
	Eff.50%	91,60
Power factor cosφ	100% load	0,85
60Hz 460/793V	Power(kW)	51,75
60Hz 480/830V	Power(kW)	54,00
Speed(60Hz)	(r/min)	1170
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	438,52
Tst/Tn (Times)	2,3
Tmax/Tn (Times)	2,3
Tmin/Tn (Times)	2,3
Ist/In (Times)	7,5
Bearings type(DE)	6316 C3
Bearings type(NDE)	6316 C3
Oil seals	80*100*10
Cable glands	2-M50*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	80
Net weight(kg)	489,50
Moment of inertia (kg*m²)	1,785480000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za