

ALPHA



Technical Data Sheet

Model T1C 160M-6

Housing material		Casting iron
Phase		Three
Frame size		160
Power(50Hz)	kW	7,50
Current(A)400V	Δ	18,00
Current(A)690V	Y	10,39
Speed(50Hz)	(r/min)	960
Efficiency	IE1	
	Eff.100%	91,90
	Eff.75%	93,30
	Eff.50%	92,50
Power factor cosφ	100% load	0,86
60Hz 460/793V	Power(kW)	8,63
60Hz 480/830V	Power(kW)	9,00
Speed(60Hz)	(r/min)	1170
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	74,61
Tst/Tn (Times)	2,3
Tmax/Tn (Times)	2,5
Tmin/Tn (Times)	2,5
Ist/In (Times)	7,5
Bearings type(DE)	6309 C3
Bearings type(NDE)	6309 C3
Oil seals	45*65*8
Cable glands	2-M32*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	73
Net weight(kg)	112,00
Moment of inertia (kg*m²)	0,087260000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za