

ALPHA



Technical Data Sheet

Model T1C 315S-6

| | | |
|--------------------------|-----------|----------------------------|
| Housing material | | Casting iron |
| Phase | | Three |
| Frame size | | 315 |
| Power(50Hz) | kW | 75,00 |
| Current(A)400V | Δ | 137,53 |
| Current(A)690V | Y | 79,73 |
| Speed(50Hz) | (r/min) | 980 |
| Efficiency | IE1 | |
| | Eff.100% | 92,60 |
| | Eff.75% | 93,40 |
| | Eff.50% | 92,20 |
| Power factor cosφ | 100% load | 0,85 |
| 60Hz 460/793V | Power(kW) | 86,25 |
| 60Hz 480/830V | Power(kW) | 90,00 |
| Speed(60Hz) | (r/min) | 1176 |
| Regulations | | IEC / DIN / ISO / VDE / EN |
| Standard | | IEC 60034 |
| Ambient Temp. | | -20°C ~ +40°C |
| Maximum altitude | | 1000 m above sea level |

| | |
|---|-------------------|
| Rated torque(N.m) | 730,87 |
| Tst/Tn (Times) | 2 |
| Tmax/Tn (Times) | 2,3 |
| Tmin/Tn (Times) | 1,3 |
| Ist/In (Times) | 7 |
| Bearings type(DE) | NU319 |
| Bearings type(NDE) | 6317C3 |
| Oil seals | 95*120*12 |
| Cable glands | 2-M63*1.5 |
| Insulation class | F |
| Protection degree | IP 55 |
| Thermal protection | Without |
| Rotation direction | Clockwise |
| Service duty | S1 |
| Balance | Half-key balanced |
| Cooling | IC 411 |
| Noise dB(A) | 85 |
| Net weight(kg) | 806,00 |
| Moment of inertia (kg*m²) | 3,259760000 |



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za