



Technical Data Sheet

Model **MS 801-4**

Housing material		Aluminum
Phase		Three
Frame size		80
Power(50Hz)	kW	0.55
Current(A)230V	Δ	2.62
Current(A)400V	Y	1.51
Speed(50Hz)	(r/min)	1400
Efficiency	IE1	
	Eff.100%	70.90
	Eff.75%	70.50
	Eff.50%	65.50
Power factor cosφ	100% load	0.74
60Hz 265/460V	Power(kW)	0.63
60Hz 276/480V	Power(kW)	0.66
Speed(60Hz)	(r/min)	1680
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	3.75
Tst/Tn (Times)	2.25
Tmax/Tn (Times)	2.55
Tmin/Tn (Times)	1.95
Ist/In (Times)	4.9
Bearings type(DE)	6204-2RZ
Bearings type(NDE)	6204-2RZ
Oil seals	20x34x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	58
Net weight(kg)	8.10
Moment of inertia (kg*m²)	0.001349986



- Bearings & Seals
- Chains & Sprockets
- Electric Motors & Drives
- Belts & Pulleys
- Gearboxes & Couplings
- Lubricants & Tools
- Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za