



Technical Data Sheet

Model **MS2 100L1-4**

Housing material		Aluminum
Phase		Three
Frame size		100
Power(50Hz)	kW	2.20
Current(A)230V	Δ	8.47
Current(A)400V	Y	4.89
Speed(50Hz)	(r/min)	1440
Efficiency	IE2	
	Eff.100%	84.30
	Eff.75%	83.90
	Eff.50%	82.50
Power factor cosφ	100% load	0.77
60Hz 265/460V	Power(kW)	2.53
60Hz 276/480V	Power(kW)	2.64
Speed(60Hz)	(r/min)	1730
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	14.59
Tst/Tn (Times)	2.9
Tmax/Tn (Times)	3.5
Tmin/Tn (Times)	2
Ist/In (Times)	7.2
Bearings type(DE)	6206-2RZ
Bearings type(NDE)	6206-2RZ
Oil seals	30x44x7
Cable glands	2-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	64
Net weight(kg)	22.40
Moment of inertia (kg*m²)	0.006728579



Bearings & Seals
 Chains & Sprockets
 Electric Motors & Drives
 Belts & Pulleys
 Gearboxes & Couplings
 Lubricants & Tools
 Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za