



## Technical Data Sheet

**Model** MS 112M-2

<b>Housing material</b>		Aluminum
<b>Phase</b>		Three
<b>Frame size</b>		112
<b>Power(50Hz)</b>	kW	4.00
<b>Current(A)230V</b>	Δ	12.61
<b>Current(A)400V</b>	Y	7.25
<b>Speed(50Hz)</b>	(r/min)	2870
<b>Efficiency</b>	IE1	
	Eff.100%	85.60
	Eff.75%	87.00
	Eff.50%	86.80
<b>Power factor cosφ</b>	100% load	0.93
<b>60Hz 265/460V</b>	Power(kW)	4.60
<b>60Hz 276/480V</b>	Power(kW)	4.80
<b>Speed(60Hz)</b>	(r/min)	3440
<b>Regulations</b>		IEC / DIN / ISO / VDE / EN
<b>Standard</b>		IEC 60034
<b>Ambient Temp.</b>		-20°C ~ +40°C
<b>Maximum altitude</b>		1000 m above sea level

<b>Rated torque(N.m)</b>	13.31
<b>Tst/Tn (Times)</b>	2.6
<b>Tmax/Tn (Times)</b>	2.85
<b>Tmin/Tn (Times)</b>	1.75
<b>Ist/In (Times)</b>	8.1
<b>Bearings type(DE)</b>	6306-2RZ
<b>Bearings type(NDE)</b>	6206-2RZ
<b>Oil seals</b>	30x44x7
<b>Cable glands</b>	2-M25*1.5
<b>Insulation class</b>	F
<b>Protection degree</b>	IP 55
<b>Thermal protection</b>	Without
<b>Rotation direction</b>	Clockwise
<b>Service duty</b>	S1
<b>Balance</b>	Half-key balanced
<b>Cooling</b>	IC 411
<b>Noise dB(A)</b>	77
<b>Net weight(kg)</b>	26.00
<b>Moment of inertia (kg*m<sup>2</sup>)</b>	0.005845385



Bearings & Seals  
 Chains & Sprockets  
 Electric Motors & Drives  
 Belts & Pulleys  
 Gearboxes & Couplings  
 Lubricants & Tools  
 Field Services

Tel: +27 11 899 0000  
 Email: [info@bearings.co.za](mailto:info@bearings.co.za)  
[www.bearings.co.za](http://www.bearings.co.za)