



Technical Data Sheet

Model MS 132S-4

| | | |
|--------------------------|-----------|----------------------------|
| Housing material | | Aluminum |
| Phase | | Three |
| Frame size | | 132 |
| Power(50Hz) | kW | 5.50 |
| Current(A)230V | Δ | 18.76 |
| Current(A)400V | Y | 10.78 |
| Speed(50Hz) | (r/min) | 1445 |
| Efficiency | IE1 | |
| | Eff.100% | 86.40 |
| | Eff.75% | 87.80 |
| | Eff.50% | 87.70 |
| Power factor cosφ | 100% load | 0.85 |
| 60Hz 265/460V | Power(kW) | 6.33 |
| 60Hz 276/480V | Power(kW) | 6.60 |
| Speed(60Hz) | (r/min) | 1735 |
| Regulations | | IEC / DIN / ISO / VDE / EN |
| Standard | | IEC 60034 |
| Ambient Temp. | | -20°C ~ +40°C |
| Maximum altitude | | 1000 m above sea level |

| | |
|---|-------------------|
| Rated torque(N.m) | 36.35 |
| Tst/Tn (Times) | 2.15 |
| Tmax/Tn (Times) | 2.85 |
| Tmin/Tn (Times) | 1.75 |
| Ist/In (Times) | 7.5 |
| Bearings type(DE) | 6308-2RZ |
| Bearings type(NDE) | 6208-2RZ |
| Oil seals | 40x58x7 |
| Cable glands | 2-M25*1.5 |
| Insulation class | F |
| Protection degree | IP 55 |
| Thermal protection | Without |
| Rotation direction | Clockwise |
| Service duty | S1 |
| Balance | Half-key balanced |
| Cooling | IC 411 |
| Noise dB(A) | 71 |
| Net weight(kg) | 39.00 |
| Moment of inertia (kg*m²) | 0.024846330 |



Bearings & Seals
 Chains & Sprockets
 Electric Motors & Drives
 Belts & Pulleys
 Gearboxes & Couplings
 Lubricants & Tools
 Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za