

ALPHA



Technical Data Sheet

Model T1C 801-2

Housing material		Casting iron
Phase		Three
Frame size		80
Power(50Hz)	kW	0,55
Current(A)400V	Δ	3,37
Current(A)690V	Y	1,95
Speed(50Hz)	(r/min)	900
Efficiency	IE1	
	Eff.100%	65,80
	Eff.75%	66,10
	Eff.50%	62,30
Power factor cosφ	100% load	0,62
60Hz 460/793V	Power(kW)	0,63
60Hz 480/830V	Power(kW)	0,66
Speed(60Hz)	(r/min)	1080
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	5,84
Tst/Tn (Times)	2,2
Tmax/Tn (Times)	2,3
Tmin/Tn (Times)	1,8
Ist/In (Times)	6
Bearings type(DE)	6204-2RZ
Bearings type(NDE)	6204-2RZ
Oil seals	20*34*7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	54
Net weight(kg)	15,00
Moment of inertia (kg*m²)	0,000930000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za