

ALPHA



Technical Data Sheet

Model T1C 100L-6

Housing material		Casting iron
Phase		Three
Frame size		100
Power(50Hz)	kW	1,50
Current(A)525V	Δ	3,00
Current(A)550V	Δ	2,87
Speed(50Hz)	(r/min)	940
Efficiency	IE1	
	Eff.100%	75,20
	Eff.75%	75,70
	Eff.50%	72,40
Power factor cosφ	100% load	0,73
60Hz 600V	Power(kW)	2
Speed(60Hz)	(r/min)	1128
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	15,24
Tst/Tn (Times)	2
Tmax/Tn (Times)	2,2
Tmin/Tn (Times)	1,8
Ist/In (Times)	5,5
Bearings type(DE)	6206-2RZ
Bearings type(NDE)	6206-2RZ
Oil seals	30*44*7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	61
Net weight(kg)	29,50
Moment of inertia (kg*m²)	0,007830000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za