

# ALPHA



## Technical Data Sheet

**Model** T1C 160L-6

|                          |           |                            |
|--------------------------|-----------|----------------------------|
| <b>Housing material</b>  |           | Casting iron               |
| <b>Phase</b>             |           | Three                      |
| <b>Frame size</b>        |           | 160                        |
| <b>Power(50Hz)</b>       | kW        | 11,00                      |
| <b>Current(A)525V</b>    | Δ         | 18,67                      |
| <b>Current(A)550V</b>    | Δ         | 17,82                      |
| <b>Speed(50Hz)</b>       | (r/min)   | 960                        |
| <b>Efficiency</b>        | IE1       |                            |
|                          | Eff.100%  | 86,40                      |
|                          | Eff.75%   | 86,70                      |
|                          | Eff.50%   | 84,40                      |
| <b>Power factor cosφ</b> | 100% load | 0,75                       |
| <b>60Hz 600V</b>         | Power(kW) | 13                         |
|                          |           |                            |
| <b>Speed(60Hz)</b>       | (r/min)   | 1152                       |
| <b>Regulations</b>       |           | IEC / DIN / ISO / VDE / EN |
| <b>Standard</b>          |           | IEC 60034                  |
| <b>Ambient Temp.</b>     |           | -20°C ~ +40°C              |
| <b>Maximum altitude</b>  |           | 1000 m above sea level     |

|   |                   |
|---|-------------------|
| <b>Rated torque(N.m)</b>                    | 109,43            |
| <b>Tst/Tn (Times)</b>                       | 2,3               |
| <b>Tmax/Tn (Times)</b>                      | 2,5               |
| <b>Tmin/Tn (Times)</b>                      | 1,5               |
| <b>Ist/In (Times)</b>                       | 7,5               |
| <b>Bearings type(DE)</b>                    | 6309C3            |
| <b>Bearings type(NDE)</b>                   | 6309C3            |
| <b>Oil seals</b>                            | 45*65*8           |
| <b>Cable glands</b>                         | 2-M32*1.5         |
| <b>Insulation class</b>                     | F                 |
| <b>Protection degree</b>                    | IP 55             |
| <b>Thermal protection</b>                   | Without           |
| <b>Rotation direction</b>                   | Clockwise         |
| <b>Service duty</b>                         | S1                |
| <b>Balance</b>                              | Half-key balanced |
| <b>Cooling</b>                              | IC 411            |
| <b>Noise dB(A)</b>                          | 73                |
| <b>Net weight(kg)</b>                       | 122,40            |
| <b>Moment of inertia (kg*m<sup>2</sup>)</b> | 0,109630000       |



Bearings & Seals  
Chains & Sprockets  
Electric Motors & Drives  
Belts & Pulleys  
Gearboxes & Couplings  
Lubricants & Tools  
Field Services

Tel: +27 11 899 0000  
Email: [info@bearings.co.za](mailto:info@bearings.co.za)  
[www.bearings.co.za](http://www.bearings.co.za)