

ALPHA



Technical Data Sheet

Model T1C 315L1-4

Housing material		Casting iron
Phase		Three
Frame size		315
Power(50Hz)	kW	160,00
Current(A)525V	Δ	234,48
Current(A)550V	Δ	223,82
Speed(50Hz)	(r/min)	1480
Efficiency	IE1	
	Eff.100%	93,80
	Eff.75%	94,00
	Eff.50%	93,50
Power factor cosφ	100% load	0,80
60Hz 600V	Power(kW)	184
Speed(60Hz)	(r/min)	1776
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	1032,43
Tst/Tn (Times)	2
Tmax/Tn (Times)	2,3
Tmin/Tn (Times)	1,3
Ist/In (Times)	7
Bearings type(DE)	NU319
Bearings type(NDE)	6317C3
Oil seals	95*120*12
Cable glands	2-M63*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	97
Net weight(kg)	1068,00
Moment of inertia (kg*m²)	3,733670000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za