

# ALPHA



## Technical Data Sheet

**Model** T1C 355M1-4

<b>Housing material</b>		Casting iron
<b>Phase</b>		Three
<b>Frame size</b>		355
<b>Power(50Hz)</b>	kW	220.00
<b>Current(A)400V</b>	Δ	379.56
<b>Current(A)690V</b>	Y	220.04
<b>Speed(50Hz)</b>	(r/min)	1480
<b>Efficiency</b>	IE1	
	Eff.100%	94.00
	Eff.75%	94.50
	Eff.50%	94.00
<b>Power factor cosφ</b>	100% load	0.89
<b>60Hz 460/793V</b>	Power(kW)	253.00
<b>60Hz 480/830V</b>	Power(kW)	264.00
<b>Speed(60Hz)</b>	(r/min)	1776
<b>Regulations</b>		IEC / DIN / ISO / VDE / EN
<b>Standard</b>		IEC 60034
<b>Ambient Temp.</b>		-20°C ~ +40°C
<b>Maximum altitude</b>		1000 m above sea level

<b>Rated torque(N.m)</b>	1419.59
<b>Tst/Tn (Times)</b>	2
<b>Tmax/Tn (Times)</b>	2.3
<b>Tmin/Tn (Times)</b>	1.3
<b>Ist/In (Times)</b>	7
<b>Bearings type(DE)</b>	NU322
<b>Bearings type(NDE)</b>	6322C3
<b>Oil seals</b>	110*130*12
<b>Cable glands</b>	2-M63*1.5
<b>Insulation class</b>	F
<b>Protection degree</b>	IP 55
<b>Thermal protection</b>	Without
<b>Rotation direction</b>	Clockwise
<b>Service duty</b>	S1
<b>Balance</b>	Half-key balanced
<b>Cooling</b>	IC 411
<b>Noise dB(A)</b>	101
<b>Net weight(kg)</b>	1560.00
<b>Moment of inertia (kg*m<sup>2</sup>)</b>	6.872000000



- Bearings & Seals
- Chains & Sprockets
- Electric Motors & Drives
- Belts & Pulleys
- Gearboxes & Couplings
- Lubricants & Tools
- Field Services

Tel: +27 11 899 0000  
Email: [info@bearings.co.za](mailto:info@bearings.co.za)  
[www.bearings.co.za](http://www.bearings.co.za)