

ALPHA



Technical Data Sheet

Model T1C 200L2-2

| | | |
|--------------------------|-----------|----------------------------|
| Housing material | | Casting iron |
| Phase | | Three |
| Frame size | | 200 |
| Power(50Hz) | kW | 37,00 |
| Current(A)525V | Δ | 50,13 |
| Current(A)550V | Δ | 47,85 |
| Speed(50Hz) | (r/min) | 2920 |
| Efficiency | IE1 | |
| | Eff.100% | 91,20 |
| | Eff.75% | 92,70 |
| | Eff.50% | 91,50 |
| Power factor cosφ | 100% load | 0,89 |
| 60Hz 600V | Power(kW) | 43 |
| | | |
| Speed(60Hz) | (r/min) | 3504 |
| Regulations | | IEC / DIN / ISO / VDE / EN |
| Standard | | IEC 60034 |
| Ambient Temp. | | -20°C ~ +40°C |
| Maximum altitude | | 1000 m above sea level |

| | |
|---|-------------------|
| Rated torque(N.m) | 121,01 |
| Tst/Tn (Times) | 2 |
| Tmax/Tn (Times) | 2,3 |
| Tmin/Tn (Times) | 1,4 |
| Ist/In (Times) | 7,5 |
| Bearings type(DE) | 6312C3 |
| Bearings type(NDE) | 6312C3 |
| Oil seals | 60*80*8 |
| Cable glands | 2-M40*1.5 |
| Insulation class | F |
| Protection degree | IP 55 |
| Thermal protection | Without |
| Rotation direction | Clockwise |
| Service duty | S1 |
| Balance | Half-key balanced |
| Cooling | IC 411 |
| Noise dB(A) | 92 |
| Net weight(kg) | 230,00 |
| Moment of inertia (kg*m²) | 0,173510000 |



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za