

ALPHA



Technical Data Sheet

Model T1C 100L2-4

Housing material		Casting iron
Phase		Three
Frame size		100
Power(50Hz)	kW	3,00
Current(A)525V	Δ	5,06
Current(A)550V	Δ	4,83
Speed(50Hz)	(r/min)	1435
Efficiency	IE1	
	Eff.100%	81,50
	Eff.75%	82,60
	Eff.50%	79,90
Power factor cosφ	100% load	0,80
60Hz 600V	Power(kW)	3
Speed(60Hz)	(r/min)	1722
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	19,97
Tst/Tn (Times)	2,2
Tmax/Tn (Times)	2,6
Tmin/Tn (Times)	2
Ist/In (Times)	7,5
Bearings type(DE)	6206-2RZ
Bearings type(NDE)	6206-2RZ
Oil seals	30*44*7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	64
Net weight(kg)	35,00
Moment of inertia (kg*m²)	0,008830000



Bearings & Seals
Chains & Sprockets
Electric Motors & Drives
Belts & Pulleys
Gearboxes & Couplings
Lubricants & Tools
Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za