

ALPHA



Technical Data Sheet

Model T1C 132S1-2

Housing material		Casting iron
Phase		Three
Frame size		132
Power(50Hz)	kW	5.50
Current(A)400V	Δ	11.16
Current(A)690V	Y	6.47
Speed(50Hz)	(r/min)	2900
Efficiency	IE1	
	Eff.100%	84.70
	Eff.75%	85.50
	Eff.50%	82.80
Power factor cosφ	100% load	0.84
60Hz 460/793V	Power(kW)	6.33
60Hz 480/830V	Power(kW)	6.60
Speed(60Hz)	(r/min)	3480
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	18.11
Tst/Tn (Times)	2.2
Tmax/Tn (Times)	2.3
Tmin/Tn (Times)	1.8
Ist/In (Times)	7.5
Bearings type(DE)	6308-2RZ
Bearings type(NDE)	6308-2RZ
Oil seals	40*58*7
Cable glands	2-M25*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	80
Net weight(kg)	57.50
Moment of inertia (kg*m²)	0.011060000



- Bearings & Seals
- Chains & Sprockets
- Electric Motors & Drives
- Belts & Pulleys
- Gearboxes & Couplings
- Lubricants & Tools
- Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za