

# ALPHA



## Technical Data Sheet

**Model** T1C 132M2-6

|                          |           |                            |
|--------------------------|-----------|----------------------------|
| <b>Housing material</b>  |           | Casting iron               |
| <b>Phase</b>             |           | Three                      |
| <b>Frame size</b>        |           | 132                        |
| <b>Power(50Hz)</b>       | kW        | 5,50                       |
| <b>Current(A)525V</b>    | Δ         | 9,84                       |
| <b>Current(A)550V</b>    | Δ         | 9,39                       |
| <b>Speed(50Hz)</b>       | (r/min)   | 950                        |
| <b>Efficiency</b>        | IE1       |                            |
|                          | Eff.100%  | 83,10                      |
|                          | Eff.75%   | 83,00                      |
|                          | Eff.50%   | 80,60                      |
| <b>Power factor cosφ</b> | 100% load | 0,74                       |
| <b>60Hz 600V</b>         | Power(kW) | 6                          |
|                          |           |                            |
| <b>Speed(60Hz)</b>       | (r/min)   | 1140                       |
| <b>Regulations</b>       |           | IEC / DIN / ISO / VDE / EN |
| <b>Standard</b>          |           | IEC 60034                  |
| <b>Ambient Temp.</b>     |           | -20°C ~ +40°C              |
| <b>Maximum altitude</b>  |           | 1000 m above sea level     |

|   |                   |
|---|-------------------|
| <b>Rated torque(N.m)</b>                    | 55,29             |
| <b>Tst/Tn (Times)</b>                       | 2                 |
| <b>Tmax/Tn (Times)</b>                      | 2,5               |
| <b>Tmin/Tn (Times)</b>                      | 1,8               |
| <b>Ist/In (Times)</b>                       | 7,5               |
| <b>Bearings type(DE)</b>                    | 6308-2RZ          |
| <b>Bearings type(NDE)</b>                   | 6308-2RZ          |
| <b>Oil seals</b>                            | 40*58*7           |
| <b>Cable glands</b>                         | 2-M25*1.5         |
| <b>Insulation class</b>                     | F                 |
| <b>Protection degree</b>                    | IP 55             |
| <b>Thermal protection</b>                   | Without           |
| <b>Rotation direction</b>                   | Clockwise         |
| <b>Service duty</b>                         | S1                |
| <b>Balance</b>                              | Half-key balanced |
| <b>Cooling</b>                              | IC 411            |
| <b>Noise dB(A)</b>                          | 69                |
| <b>Net weight(kg)</b>                       | 65,00             |
| <b>Moment of inertia (kg*m<sup>2</sup>)</b> | 0,048900000       |



Bearings & Seals  
Chains & Sprockets  
Electric Motors & Drives  
Belts & Pulleys  
Gearboxes & Couplings  
Lubricants & Tools  
Field Services

Tel: +27 11 899 0000  
Email: [info@bearings.co.za](mailto:info@bearings.co.za)  
[www.bearings.co.za](http://www.bearings.co.za)