

# Technical Data

## PENETRATING SPRAY

ROCOL Penetrating Spray is a powerful penetrating fluid, with molybdenum disulphide, in an aerosol. A powerful jet application of lubricant that penetrates to give quick and effective release of corroded threaded fasteners or similar seized components. It contains molybdenum disulphide, to aid disassembly, and corrosion inhibitors to provide a protective film against further corrosive attack.

### Features

- Excellent penetration of rust, scale, grease, oil etc...
- Molybdenum disulphide aids dismantling.
- Protective film provides short term corrosion protection.
- Fast acting performance.

### Directions for Use

- Ideally remove any excessive oil, grease or dirt contamination.
- Shake can, and coat thoroughly from approximately 10-30cm.
- In severe cases a second coating a few minutes later may prove beneficial.
- Allow time for penetration to occur before attempting to release.
- Test compatibility with painted and coated surfaces and rubbers prior to application.

Technical and Safety Data Sheets are available from:

ROCOL LUBRICANTS SA (PTY) LTD  
 Fax: (011) 462 1693  
 Tel: (011) 462 1730

Issue: 14021 01/04/2014

**ROCOL Lubricants South Africa (Pty) Ltd**

Registered Company No. 1982/000842/07

T +27 (0) 11 462 1730 • F +27 (0) 11 462 1693 • E sales@rocol.co.za • [www.rocol.co.za](http://www.rocol.co.za)

Units 5 & 6 Meadowbrook Business Estate, Jacaranda Avenue, Olivedale, Randburg • PO Box 755 Cramerview 2060, Johannesburg, South Africa

Manufacturers and Distributors of:



ROCOL Lubricants



LPS Laboratories



Chemtronics



Hawk Automotive

Director: S.J. Daley (Managing)

# Technical Data

## PENETRATING SPRAY

Appearance	Pale Amber Liquid
Solids	Molybdenum Disulphide
Penetrant	Blend of mineral oil and hydrocarbon solvents
Propellant	CO <sub>2</sub> (Carbon Dioxide)
Storage	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
Pack Size	300ml

Technical and Safety Data Sheets are available from:

ROCOL LUBRICANTS SA (PTY) LTD

Fax: (011) 462 1693

Tel: (011) 462 1730

Issue: 14021 01/04/2014

### ROCOL Lubricants South Africa (Pty) Ltd

Registered Company No. 1982/000842/07

T +27 (0) 11 462 1730 • F +27 (0) 11 462 1693 • E [sales@rocol.co.za](mailto:sales@rocol.co.za) • [www.rocol.co.za](http://www.rocol.co.za)

Units 5 & 6 Meadowbrook Business Estate, Jacaranda Avenue, Olivedale, Randburg • PO Box 755 Cramerview 2060, Johannesburg, South Africa

Manufacturers and Distributors of:



ROCOL Lubricants



LPS Laboratories



Chemtronics



Hawk Automotive

Director: S.J. Daley (Managing)