



Technical Data Sheet

Model MS 90L1-2

Housing material		Aluminum
Phase		Three
Frame size		90
Power(50Hz)	kW	2.20
Current(A)230V	Δ	7.84
Current(A)400V	Y	4.51
Speed(50Hz)	(r/min)	2860
Efficiency	IE1	
	Eff.100%	82.90
	Eff.75%	83.40
	Eff.50%	81.40
Power factor cosφ	100% load	0.85
60Hz 265/460V	Power(kW)	2.53
60Hz 276/480V	Power(kW)	2.64
Speed(60Hz)	(r/min)	3430
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	7.35
Tst/Tn (Times)	4.2
Tmax/Tn (Times)	3.9
Tmin/Tn (Times)	3.3
Ist/In (Times)	8.2
Bearings type(DE)	6205-2RZ
Bearings type(NDE)	6205-2RZ
Oil seals	25x37x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	72
Net weight(kg)	14.50
Moment of inertia (kg*m²)	0.002123029



Bearings & Seals
 Chains & Sprockets
 Electric Motors & Drives
 Belts & Pulleys
 Gearboxes & Couplings
 Lubricants & Tools
 Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za